

CLINCHNUT, FLUSH MOUNTED, SELF-LOCKING




TABLE I - DIMENSIONS AND DASH NUMBERS

NAFCO DASH NUMBER	THREAD (AS8879)	A +.001 -.005	B REF	ØC ±.005	ØD MIN	E ±.010	H MAX	ØW MAX	APPROX. WEIGHT LBS./100
NA2097-26-4	.0860-56 UNJC-3B	.040	.025	.132	.087	.040	.110	.192	.03
NA2097-26-6		.060				.03			
NA2097-40-4	.1120-40 UNJC-3B	.040	.025	.163	.113	.040	.124	.223	.04
NA2097-40-6		.060				.04			
NA2097-40-9		.090				.05			
NA2097-62-4	.1380-32 UNJC-3B	.040	.025	.195	.142	.040	.141	.254	.06
NA2097-62-6		.060				.06			
NA2097-62-9		.090				.07			
NA2097-82-4	.1640-32 UNJC-3B	.040	.025	.230	.168	.040	.170	.285	.10
NA2097-82-6		.060				.10			
NA2097-82-9		.090				.11			
NA2097-02-4	.1900-32 UNJF-3B	.040	.032	.257	.194	.040	.188	.348	.15
NA2097-02-6		.060				.15			
NA2097-02-9		.090				.17			

MATERIAL: NO CODE -- CARBON STEEL, GRADE 1018 PER ASTM A510, HEAT TREATED.
"C" CODE -- A-286 CORROSION RESISTANT STEEL PER AMS5731, AMS5732, AMS5734 OR AMS5737.

FINISH: NO CODE -- CADMIUM PLATED PER QQ-P-416 TYPE II, CLASS 3. NAFCO MOLYBDENUM DISULFIDE LUBRICANT OPTIONAL.
"C" CODE -- PASSIVATED PER QQ-P-35. NAFCO MOLYBDENUM DISULFIDE LUBRICANT OPTIONAL. SILVER PLATE PER AMS2410 OPTIONAL.

SERVICE TEMP: NO CODE -- TO 450°F.
"C" CODE -- SILVER PLATED -- TO 800°F.
NON-SILVER PLATED -- TO 450°F.

CONFORMS TO:
NASM25027
AS8879
K7000/K7001

NAFCO USA, LLC
CARSON CITY, NV 89706

PART NUMBER
NA2097, NA2097C
FSC / CAGE CODE: 32387