



BULKHEAD NUTSTRAP, SELF-LOCKING, LOW PERMEABILITY

MATERIAL: PLATE-- 2024-T3 ALUMINUM PER AMS-QQ-A-250/4.
NUT -- TYPE 303 CRES PER ASTM A581 OR ASTM A582.

FINISH: PLATE--ALODINE PER MIL-DTL-5541.
NUT-- PASSIVATED PER AMS2700 PLUS DRY FILM LUBRICANT PER AS5272.

SERVICE TEMP: TO 250° F

VARIATIONS: FOR OTHER SIZES AND MATERIALS CONTACT NAFCO USA, LLC.

APPLICATION: FOR USE IN LIEU OF SELF-LOCKING HEX NUTS FOR MOUNTING ELECTRICAL RECEPTACLES TO BULKHEADS OR FLANGES, ETC.
CONFORMS TO MIL-C-85528/2.

NOTES: 1. THE JIFFYNUT IS A MECHANICALLY LOCKED-IN SELF-LOCKING NUT MEETING THE REQUIREMENTS OF NASM45938.

EXAMPLE CALLOUT:

NA2188-15

NO. 19 SHELL SIZE

BASIC PART NUMBER

SHEET 2 OF 2

CONFORMS TO:

NASM45938
AS8879
MIL-C-85528/2

NAFCO USA, LLC

CARSON CITY, NV 89706

PART NUMBER

NA2188

FSC / CAGE CODE: 32387