



NUT, CASTELLATED, SPANNER-END SLOTS

TABLE B - DIMENSIONS AND DASH NUMBERS

DASH NUMBER	THREAD T (AS8879)	A +.015 -.000	B +.000 -.015	C +.000 -.006	D ±.010	E ±.010	F ±.010	G +.010 -.000	H +.005 -.010	J	K	L ±1°0'	APPROX. WEIGHT LBS/100
NA2371-02	.3750-32 UNJEF-3B	.375	.300	.598	.170	.170	.094	.125	.525	4	4	45°	1.33
NA2371-03	.4375-28 UNJEF-3B	.438	.300	.748	.170	.170	.094	.125	.675	6	3	30°	2.13
NA2371-04	.5000-28 UNJEF-3B	.500	.300	.798	.170	.170	.094	.125	.725	6	3	30°	2.28
NA2371-05	.5625-24 UNJEF-3B	.562	.300	.858	.170	.170	.094	.125	.785	6	3	30°	2.42
NA2371-06	.6250-24 UNJEF-3B	.625	.300	.923	.170	.170	.094	.187	.850	6	3	30°	2.62
NA2371-07	.6875-24 UNJEF-3B	.688	.300	.998	.170	.170	.094	.187	.925	6	3	30°	3.06
NA2371-08	.7500-20 UNJEF-3B	.750	.300	1.073	.170	.170	.094	.187	1.000	6	3	30°	3.47
NA2371-09	.8125-20 UNJEF-3B	.812	.300	1.133	.170	.170	.094	.187	1.060	8	4	22°30'	3.50
NA2371-10	.8750-20 UNJEF-3B	.875	.300	1.198	.170	.170	.094	.187	1.125	8	4	22°30'	3.86
NA2371-11	.9375-20 UNJEF-3B	.938	.300	1.273	.170	.170	.094	.187	1.200	8	4	22°30'	4.28
NA2371-12	1.0000-20 UNJEF-3B	1.000	.300	1.348	.170	.170	.094	.187	1.275	8	4	22°30'	4.78
NA2371-13	1.0625-18 UNJEF-3B	1.062	.325	1.408	.185	.195	.094	.187	1.335	8	4	22°30'	5.50
NA2371-14	1.1250-18 UNJEF-3B	1.125	.325	1.473	.185	.195	.094	.187	1.400	8	4	22°30'	5.89
NA2371-15	1.1875-18 UNJEF-3B	1.188	.325	1.548	.185	.195	.094	.250	1.475	8	4	22°30'	6.12
NA2371-16	1.2500-18 UNJEF-3B	1.250	.325	1.623	.185	.195	.094	.250	1.550	8	4	22°30'	6.68
NA2371-17	1.3125-18 UNJEF-3B	1.312	.325	1.683	.185	.195	.094	.250	1.610	8	4	22°30'	6.95
NA2371-18	1.3750-18 UNJEF-3B	1.375	.325	1.748	.185	.195	.094	.250	1.675	8	4	22°30'	7.42
NA2371-19	1.4375-18 UNJEF-3B	1.438	.325	1.823	.185	.195	.094	.250	1.750	8	4	22°30'	8.07
NA2371-20	1.5000-18 UNJEF-3B	1.500	.325	1.898	.185	.150	.125	.250	1.800	10	5	18°	8.44
NA2371-21	1.5625-16 UNJ-3B	1.562	.325	1.958	.185	.150	.125	.250	1.860	10	5	18°	8.68
NA2371-22	1.6250-16 UNJ-3B	1.625	.325	2.023	.185	.150	.125	.250	1.925	10	5	18°	9.28
NA2371-23	1.6875-16 UNJ-3B	1.688	.325	2.098	.175	.150	.125	.250	2.000	10	5	18°	9.58
NA2371-24	1.7500-16 UNJ-3B	1.750	.325	2.173	.175	.150	.125	.250	2.075	10	5	18°	10.38
NA2371-25	1.8125-16 UNJ-3B	1.812	.325	2.233	.175	.150	.125	.250	2.135	10	5	18°	10.76
NA2371-26	1.8750-16 UNJ-3B	1.875	.325	2.298	.175	.150	.125	.250	2.200	10	5	18°	11.32
NA2371-27	1.9375-16 UNJ-3B	1.938	.325	2.373	.175	.150	.125	.312	2.275	10	5	18°	11.42
NA2371-28	2.0000-16 UNJ-3B	2.000	.325	2.448	.175	.150	.125	.312	2.350	10	5	18°	12.22
NA2371-29	2.0625-16 UNJS-3B	2.062	.375	2.480	.210	.200	.125	.312	2.385	10	5	18°	13.78
NA2371-30	2.1250-16 UNJ-3B	2.125	.375	2.545	.210	.200	.125	.312	2.450	10	5	18°	14.29
NA2371-31	2.1875-16 UNJS-3B	2.188	.375	2.620	.210	.200	.125	.312	2.525	10	5	18°	15.20
NA2371-32	2.2500-16 UNJ-3B	2.250	.375	2.695	.210	.200	.125	.312	2.600	10	5	18°	16.30
NA2371-33	2.3125-16 UNJS-3B	2.312	.375	2.755	.210	.200	.125	.375	2.660	10	5	18°	15.90
NA2371-34	2.3750-16 UNJ-3B	2.375	.375	2.820	.210	.200	.125	.375	2.725	10	5	18°	16.42
NA2371-35	2.4375-16 UNJS-3B	2.438	.375	2.895	.210	.200	.125	.375	2.800	10	5	18°	17.52
NA2371-36	2.5000-16 UNJ-3B	2.500	.375	2.970	.210	.155	.187	.375	2.850	10	5	18°	18.50
NA2371-37	2.5625-16 UNJS-3B	2.562	.375	3.030	.210	.155	.187	.375	2.910	10	5	18°	18.90
NA2371-38	2.6250-16 UNJ-3B	2.625	.375	3.095	.210	.155	.187	.375	2.975	10	5	18°	19.60
NA2371-39	2.7500-16 UNJ-3B	2.750	.375	3.245	.205	.155	.187	.375	3.125	10	5	18°	21.60
NA2371-40	2.8750-16 UNJ-3B	2.875	.375	3.370	.205	.155	.187	.375	3.250	10	5	18°	22.72
NA2371-41	3.0000-16 UNJ-3B	3.000	.375	3.520	.205	.155	.187	.375	3.400	10	5	18°	25.10

THIS STANDARD HAS DEVELOPED COOPERATIVELY WITH MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIVISION.

CONFORMS TO:
NASM25027
AS8879

NAFCO USA, LLC
CARSON CITY, NV 89706

PART NUMBER
NA2371
FEDERAL SUPPLY CODE: 32387