

# NUT, PLATE, SELF-LOCKING, NON-METALLIC INSERT, FLOATING, TWO LUG




TABLE I - DIMENSIONS AND DASH NUMBERS

DASH NUMBERS		T THREAD SIZE	A MAX	B		C ±.005	F MIN	ØG ±.010	H	
PLAIN HOLES	CSK OR DIMPLED HOLES			MAX	MIN				MAX	MIN
NA2369-40	NA2369-40BC	.1120-40 UNJC-3B	.984	.416	.328	.344	.115	.200	.218	.140
NA2369-62	NA2369-62BC	.1380-32 UNJC-3B	.984	.416	.328	.344	.115	.200	.234	.160
NA2369-82	NA2369-82BC	.1640-32 UNJC-3B	.984	.416	.328	.344	.115	.200	.312	.234
NA2369-02	NA2369-02BC	.1900-32 UNJF-3B	.984	.416	.328	.344	.115	.200	.312	.234
NA2369-048	NA2369-048BC	.2500-28 UNJF-3B	1.296	.516	.406	.500	.115	.200	.387	.283
NA2369-054	NA2369-054BC	.3125-24 UNJF-3B	1.296	.609	.484	.500	.115	.230	.387	.283
NA2369-064	NA2369-064BC	.3750-24 UNJF-3B	1.296	.641	.563	.500	.115	.230	.479	.439
NA2369-070	/2/	.4375-20 UNJF-3B	1.477	.719	.672	.562	.146	/2/	.504	.470
NA2369-080	/2/	.5000-20 UNJF-3B	1.602	.859	.796	.625	.146	/2/	.630	.596

DASH NUMBERS		J ±.010	ØK /1/ +.015 -.000	ØP		V MAX	ØW MIN	AXIAL STRENGTH LBF MIN	WEIGHT LB/100
PLAIN HOLES	CSK OR DIMPLED HOLES			MAX	MIN				
NA2369-40	NA2369-40BC	.688	.098	.260	.198	.075	.112	750	.55
NA2369-62	NA2369-62BC	.688	.098	.260	.198	.075	.138	1,130	.55
NA2369-82	NA2369-82BC	.688	.098	.270	.224	.075	.164	1,720	.60
NA2369-02	NA2369-02BC	.688	.098	.270	.250	.075	.190	2,460	.60
NA2369-048	NA2369-048BC	1.000	.098	.330	.310	.075	.250	4,580	1.20
NA2369-054	NA2369-054BC	1.000	.130	.393	.373	.075	.312	7,390	2.20
NA2369-064	NA2369-064BC	1.000	.130	.455	.435	.075	.375	11,450	2.80
NA2369-070	/2/	1.123	.161	.517	.497	.115	.437	15,450	3.30
NA2369-080	/2/	1.250	.161	.580	.560	.115	.500	21,110	4.00

CONFORMS TO:  
NASM25027  
AS8879

**NAFCO USA, LLC**  
CARSON CITY, NV 89706

PART NUMBER  
**NA2369**  
FSCM / CAGE CODE: 32387