



# CLINCHNUT, FLUSH MOUNTED, SELF-LOCKING

**VARIATIONS:** M -- ADD BEFORE FIRST DASH NO. FOR OPTIONAL DRY FILM LUBRICANT. EXAMPLE: NA2097CM-02-1.  
S -- ADD BEFORE FIRST DASH NO. FOR OPTIONAL SILVER PLATING. EXAMPLE: NA2097CS-02-1.

**APPLICATION:** A PRESS-IN / FLARED SKIRT NUT FOR USE IN THIN ALUMINUM AND MAGNESIUM SHEETS, GRAPHITE COMPOSITE AND FIBER-REINFORCED PLASTIC SHEETS, PRINTED CIRCUIT BOARDS, ETC.

**EXAMPLE CALLOUT:**

NA2097 C S - 02 - 6

↑ SHANK LENGTH (SEE TABLE I)  
↑ .1900-32 THREAD (SEE TABLE I)  
↑ SILVER PLATE (SEE VARIATIONS SECTION)  
↑ CORROSION RESISTANT STEEL (SEE MATERIAL SECTION)  
↑ BASIC PART NUMBER (SEE TABLE I)

**NOTES:**

- (1) SEE PAGE 2.32 FOR INSTALLATION PROCEDURE AND RECOMMENDED TOOLING.
- (2) FOR OTHER FINISHES AND MATERIALS CONTACT NAFCO USA, LLC.

CONFORMS TO:

NASM25027  
AS8879  
K7000/K7001

**NAFCO USA, LLC**  
CARSON CITY, NV 89706

PART NUMBER

**NA2097, NA2097C**

FSC / CAGE CODE: 32387